

Fibrecrete

Topping Stone

Product Description

Fibrecrete Topping Stone is a high PSV aggregate used in concrete and/or asphalt repair applications of hot-applied mastics conforming to ASTM D8260-20 specifications.

Basic Uses

Fibrecrete Topping Stone is used in mastic repair of large cracks, spalls and potholes in asphalt and concrete.

Features and Benefits

- Surface Protection
- Skid Resistance
- Blends repaired surface into aged concrete and oxidated asphalt

Physical Properties*

Property		Value
Color		Grey
Moisture %		0.2 maximum
Sieve Analysis	Sieve Size	Typical % Passing
	#4	100
	#16	0-3
	#30	0-1

Packaging

- 50-pound bag

Health and Safety

See SDS for complete safety precautions prior to use. Use HSE-approved personal protective equipment (PPE), including safety glasses, gloves and confined space equipment/procedures if applicable. Avoid skin contact; do not ingest. For professional use only.

Installation

Topping Stone must be dry. Prior to use, apply a torch to unbagged Topping Stone to eliminate residual surface moisture.

Once the top layer of Fibrecrete G has been screeded to a level grade, apply Topping Stone by hand to fully cover the Fibrecrete G. Once Fibrecrete G has cooled, remove loose Topping Stone by sweeping the surface.

All removed materials and residual repair materials will be recovered and disposed of away from the site according to the client's specifications. All Federal, State and OSHA safety requirements must be followed during installation.

Limitations/ Shelf Life

Five (5) years when stored in a dry place in original, closed packaging. Optimal storage temperature: 60 to 70 °F (15 to 20 °C).

Warranty

FPT Infrastructure warrants its Products to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, FPT Infrastructure makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to FPT Infrastructure Products. FPT Infrastructure's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of FPT Infrastructure Products proven to be defective, and FPT Infrastructure shall not be liable for any loss or damage.

Please refer to our website at fptinfrastructure.com for the most up-to-date Product Data Sheets.

NOTE: All FPT Infrastructure Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements