Safety Data Sheet

Prepared In Accordance With HCS
29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier

INFMMLM-SDS

Revision Date: 11/05/2026

Product Name: Matacryl Manual LM

Supersedes Date: 01/10/2025

1.2 Relevant identified uses of the substance or mixture and uses advised against

Component of multicomponent coatings - Industrial and professional use. Advised against: others than recommended

1.3 Details of the supplier of the safety data sheet

Supplier:

FPT Infrastructure, Division of Fibrecrete Preservation Technologies, Inc.
401 Old US 52 South
Mount Airy, NC 27030
USA
Phone: (336) 789 7259
Fax: (336) 789 7425
www.fptinfrastructure.com
info@fptinfrastructure.com

Datasheet Produced by: EHS@FPTInfrastructure.com

1.4 Emergency telephone number:

+1 703-741-5970 - North America
+1 800-424-9300
+55 11 4349 1359 - South America
+52 55 8526 4930 - Central America
+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, And Africa
+65 3163 8374 - Asia, South Asia, And Oceania

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 3
Flammable Liquid, category 2
Skin Irritation, category 2
Skin Sensitizer, category 1
STOT, single exposure, category 3, RTI

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Methyl methacrylate

HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

Name According to EEC	EINEC No.	CAS-No.	%	Classifications

Methyl methacrylate	201-297-1	80-62-6	10 - <30	H225-315-317-335	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3 RTI
Dodecand-1-thiol		112-55-0	0.1 - <1.0	H314-317-400-410	Aquatic Acute 1, Aquatic Chronic 1, Skin Corr. 1, Skin Sens. 1

CAS-No. **M-Factors**

80-62-6
112-55-0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.
AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention. Provide fresh air, rest and warmth. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position.
AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin.
AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.
AFTER INGESTION: If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

May cause sensitization by skin contact. Irritating to eyes, respiratory system and skin. May cause headache and dizziness. Acts as a defatting agent on skin.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11. When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

Fire will produce dense black smoke containing hazardous combustion products (see section 10). Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Open drum carefully as content may be under pressure. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.
PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources. Ultraviolet light.
STORAGE CONDITIONS: Keep at temperatures between 5 and 25 °C. Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store away from: oxidising materials, acids, and alkalis. Store in upright position only. Storage of flammable liquids.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
Methyl methacrylate	80-62-6	50 PPM	100 PPM	
Dodecand-1-thiol	112-55-0	0.1 PPM		

Name	CAS-No.	OSHA PEL	OSHA STEL
Methyl methacrylate	80-62-6	410 MGM3, 100 PPM	
Dodecand-1-thiol	112-55-0		

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Use compressed air or fresh air breathing apparatus in closed compartments. Wear respiratory protection with combination filter (dust and gas filter, EN 14387:2004+A1:2008) during spraying operations: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust).

EYE PROTECTION: If splashes are likely to occur, wear: Face-shield, tightly fitting safety goggles (EN 166).

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

Body Protection: Long sleeved clothing.
Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Viscous liquid
Physical State	Liquid
Odor	Characteristic
Odor threshold	0.05 ppm
pH	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	100.3 - N.D.
Flash Point, (°F / °C)	11.5 C 52.7 F
Evaporation rate	Slower than Ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits - %(V)	2.1 - 12.5
Vapour Pressure	38.7 mbar
Vapour density	Not determined
Relative density	1.23
Solubility in / Miscibility with water	Not determined
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined

Viscosity	300-700 mPa.s
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	Not determined
Specific Gravity (g/cm3)	1.230

10. Stability and Reactivity

10.1 Reactivity
No reactivity hazards known under recommended storage and use conditions.

10.2 Chemical stability
The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerise with heat evolution. Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions
May polymerise in the presence of radical forming agents and reducing agents with evolution of heat.

10.4 Conditions to avoid
Avoid heat, sparks, flames and other ignition sources. Ultraviolet light.

10.5 Incompatible materials
Strong oxidizing agents. Strong acids. Reducing agents. Avoid radical-forming starting agents, peroxides and reactive metals. Tertiary amines. Sulphur compounds.

10.6 Hazardous decomposition products
No decomposition if stored and applied as directed. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide (CO), carbon dioxide (CO2), oxides of nitrogen (NOx).

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
80-62-6	Methyl methacrylate	7872 mg/kg (oral, rat)	>5000 mg/kg	3750 ppm (inhalation, rat)	0.000	0.000

Additional Information:

Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Chronic exposure causes drying effect on the skin and eczema. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): No information

IC50 72hr (Algae): No information

LC50 96hr (fish): No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
80-62-6	Methyl methacrylate	720 mg/l	No information	125.5 - 275.0 mg/l
112-55-0	Dodecand-1-thiol	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

14. Transport Information

14.1 UN number UN1866

14.2 UN proper shipping name Resin solution, flammable

Technical name Not applicable

14.3 Transport hazard class(es) 3

Subsidiary shipping hazard Not applicable

14.4 Packing group II

14.5 Environmental hazards Yes

14.6 Special precautions for user Not applicable

EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.	%
Methyl methacrylate	80-62-6	28

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:	Not applicable
EPA VOC Content Limit (g/l):	Not determined
Product VOC Content (g/l)	Not applicable
Thinning Recommendations:	Not applicable
Application Recommendations:	Not applicable

* As per the federal EPA definition for coating categories in 40 CFR 59.401.
** Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
Blocked Prepolymer	402820-50-2
barium sulfate	7727-43-7
Pollymethylmethacrylate	025608-33-7
iron oxide	1317-61-9

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
Blocked Prepolymer	402820-50-2
barium sulfate	7727-43-7
Pollymethylmethacrylate	025608-33-7

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt. The following chemicals are listed on the NDSL; 103671-44-9 All other components of this product are listed on Canadian DSL or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS:



WARNING

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects and other reproductive harm.

Chemical Name	CAS-No.
No components listed as Prop Toxin	

CALIFORNIA PROPOSITION 65 CARCINOGENS:



WARNING

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

Chemical Name	CAS-No.
No components listed as Prop Toxin	

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Reasons for revision

Revision Report Changed
Substance and/or Product Properties Changed in Section(s):
01 - Identification
08 - Exposure Controls/Personal Protection
15 - Regulatory Information
Revision Statement(s) Changed

This is a new Safety Data Sheet (SDS). .

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in

Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.